DOWNLIGHT OM SERIES LED
VOL.5

11331

FEATURES

Slot mounted LED single multi spot system (OM3 シリーズ)

Housing

一体型ボディ構造で強力な放熱性能を実現.

Trim Color

ホワイトオプション

Reflector

NGR(ノングレアレフレクター)技術を適用した視覚的な心地よさ及び最適な光の品質で視覚的なストレスを最小化.

防塵とスクラッチ防止処理技術適用.

Optic

20° 又は 30° 配光角が可能.

Tunable Temperature

CRI 80 2700K ~ 5000K (Standard)

CRI 90 2700K ~ 6500K (Option)




Product ordering number **11331B-8TH-015-020**

SPECIFICATIONS

INDEX		DATA	
DIMENSION	mm	W105 X L110 X H95.5	
WEIGHT	Kg	0.4	
OPERATING VOLTAGE	V	AC 100~240V	
POWER CONSUMPTION	W	9	7
OUTPUT POWER	W	7.5	5.5
COLOR TEMPERATURE	K	2700	5000
LUMINOUS FLUX	lm	490	380
LOR	-	0.98	0.98
COLOR RENDERING INDEX	Ra	Over 80	
BEAM ANGLE	°	20	
IP RATING	-	20	
STORAGE HUMIDITY	%	20% ~ 70%	
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C	
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C	

SMPS (separately be ordered)



INDEX	ORDER NUMBER	NOTE
1-10 Dimming	81012	2 Drivers
DALI Dimming	82008	
DALI Dimming	82017	JAPAN
DMX Dimming	85000	

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT OM SERIES LED


11331

PHOTOMETRIC DATA

2700K


m	20° Ø(m)	lux(center/side)
1	0.39	2098/1035
2	0.78	524/258
3	1.17	233/115







5000K

m	20° Ø(m)	lux(center/side)
1	0.41	1436/745
2	0.81	359/186
3	1.22	159/82





DRAWING DATA



NOTES


Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr

DOWNLIGHT OM SERIES LED

11331

INSTALLATION INSTRUCTIONS



NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr