DOWNLIGHT O SERIES LED
VOL.5

11206

FEATURES

LED ピンホール(Pinhole)タイプ(O2シリーズ)

Housing

一体型ボディ構造で強力な放熱性能を実現.

Optic

ビーム角 20° が可能. (UGR<13)




Product ordering number **11206W-827H-003-020**
11206W-830H-003-020
11206W-840H-003-020

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	Ø65 X H51
WEIGHT	Kg	0.15
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	3.5 (with power supply unit)
OUTPUT POWER	W	2
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	220
LOR	-	0.66
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	20
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS



INDEX	ORDER NUMBER	NOTE
ON/OFF	80000	
ON/OFF	80032	JAPAN

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr

DOWNLIGHT O SERIES LED


11206


PHOTOMETRIC DATA

UGR =11.9


20°


m	Ø(m)	lux(center/side)
1	0.35	1119/598
2	0.71	280/149
3	1.06	124/66






DRAWING DATA








Ø55

W 0.15Kg

INSTALLATION INSTRUCTIONS



NOTES

Attention Read carefully before installing.

The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.

The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr