DOWNLIGHT O SERIES LED
VOL.5

11205

FEATURES

LEDダウンライト(O2シリーズ)

Housing

一体型ボディ構造で強力な放熱性能を実現.

Reflector

NGR(ノングレアレフレクター)技術を適用し
た視覚的な心地よさ及び最適な光の品質で視覚的なストレスを最小化.
防塵とスクラッチ防止処理技術適用.

Optic

ビーム角 20° が可能. (UGR<13)




Product ordering number **11205C-827H-003-020**
11205C-830H-003-020
11205C-840H-003-020

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	Ø65 X H51
WEIGHT	Kg	0.15
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	3.5 (with power supply unit)
OUTPUT POWER	W	2
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	220
LOR	-	0.71
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	20
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS



INDEX	ORDER NUMBER	NOTE
ON/OFF	80000	
ON/OFF	80032	JAPAN

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr

DOWNLIGHT O SERIES LED


11205


PHOTOMETRIC DATA

UGR =7.8


20°

m	Ø(m)	lux(center/side)
1	0.35	1108/608
2	0.71	277/152
3	1.06	123/68






DRAWING DATA



Ø55
W 0.15Kg

INSTALLATION INSTRUCTIONS



NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr