DOWNLIGHT OM SERIES LED
VOL.5

11235

FEATURES

LED Spot ダウンライト(OM2 Trimless シリーズ)

Housing

一体型ボディ構造で強力な放熱性能を実現.

Reflector

NGR(ノングレアレフレクター)技術を適用した視覚的な心地よさ及び最適な光の品質で視覚的なストレスを最小化.

(ホワイトリフレクター75° タイプ)

防塵とスクラッチ防止処理技術適用.




Product ordering number **11235B-827H-010-060**
11235B-830H-010-060
11235B-840H-010-060

SPECIFICATIONS

INDEX		DATA
DIMENSION	mm	W139 X L139 X H108.5
WEIGHT	Kg	0.45
OPERATING VOLTAGE	V	AC 100~240V
POWER CONSUMPTION	W	8.5 (with power supply unit)
OUTPUT POWER	W	7.5
COLOR TEMPERATURE	K	2700 / 3000 / 4000
LUMINOUS FLUX	lm	600
LOR	-	0.60
COLOR RENDERING INDEX	Ra	Over 80
BEAM ANGLE	°	60
IP RATING	-	20
STORAGE HUMIDITY	%	20% ~ 70%
STORAGE TEMPERATURE	˚C	-40˚C ~ +50˚C
OPERATING TEMPERATURE	˚C	-20˚C ~ +50˚C

SMPS




INDEX	ORDER NUMBER	NOTE
ON/OFF	80001	
1-10 Dimming	81000	
DALI Dimming	82006	
ON/OFF	80005	JAPAN
PWM Dimming	84000	JAPAN
DALI Dimming	82020	JAPAN
Triac Dimming	83007	AC 220~240V


ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr


DOWNLIGHT OM SERIES LED

11235


PHOTOMETRIC DATA








DRAWING DATA



INSTALLATION INSTRUCTIONS



NOTES

Attention Read carefully before installing.
The safety of this fixture is guaranteed only if you comply with these instructions. Save these instructions for future use.
The operating temperature is between -20˚C and +50˚C.

ALTO LIGHTING CO., LTD www.alto.co.kr
H-Tower,15, Beodeunaru-ro, Yeongdeungpo-gu, Seoul, Republic of Korea
Tel. 82.2.2176.1746 Fax. 82.2.2176.1781 altoled@alto.co.kr